

ULTIMATE PRO-MOTION

Continuous motion high speed side sealer



Ultimate[®] is a registered trademark of PackPark

ULTIMATE PRO-MOTION

Continuous motion high speed side sealer

ADVANTAGES

- Nonstop operation with continuous motion system
- Dual axis servo motor driven cross sealing
- High precision and consistency with cross and side seal
- Packaging with no length limit
- Control of film quantity on the 4 sides of packages for saving results
- Minimized layout requirement by compact single-chassis design
- Reduced energy & increased safety

FEATURES

- Touch control panel with color screen
- Encoder controlled speed & length aware synchronization
- Easy format change for different package sizes
- Regular or finger pitch conveyors for feeding can be applied
- Ergonomic operator panel with most useful hard buttons
- Up-to-date safety electric and mechanic measures of CE directives
- Cross and continuous knives with PID controlled heaters
- Automatic film dispenser with tension control
- Photocell controlled package distance positioned feeding
- Automatic length detection option

SEALING

- Film sealing under no distortion with non stop and tight operation
- Up to 15% advantage in film consumption
- Film tension releasing on the cross-sealing point

- Trim winder is designed to control very thin films without breakage
- Height adjustable cross sealer (Optional motorized)
- Adjustable "Central Sealing" for varied package height applications

FLEXIBILITY


- Native languages can be applied
- Recipe application with different package dimensions
- Warning messages for potential emergency cases
- "Navigation Control" for actual throughput and estimated packs/time units

OPTIONAL

- Double seal feature on cross sealer for high thickness or PE material
- Control of external infeed conveyor through operator panel
- Vertical photocell to detect thin packages
- Printed marker registered film detection & application

QUALITY


- ISO 9001 quality standard with the relevant norm's confirmations
- CE marking
- One year warranty on non-wearable parts
- Manufacturer's guarantee for spare part & after sales support



Technical specifications

	Ultimate Pro-Motion 20	Ultimate Pro-Motion 40	Ultimate Pro-Motion 60	Ultimate Pro-Motion 80
Sealer Opening: 250mm (10")	Cross Sealer Length: 400mm (16")	540mm (21")	730mm (29")	930mm (37")
Max. Speed: 30mt/min	Conveyor Belt Width: 200mm (8")	400mm (16")	600mm (24")	800mm (31")
Max. Cycle: 110 packs/min*	Max. Film Width: 700mm (28")	700mm (28")	1000mm (39")	1000mm (39")
Max. Roll Diameter: Ø 270mm (11")	Installed Power: 400V-3Ph, 8A, 6 kW	400V-3Ph, 9A, 6,8kW	400V-3Ph, 9A, 7,2kW	400V-3Ph, 10A, 7,5kW
Working Height: 860mm (+50mm) (34")	Average Consump.: 3kW	4kW	5kW	5,5kW
Air Supply: 7-40 µm PO, PP " V " Knife	Dimens. (AxBxC): 1350x3250x1480mm (53x128x58")	1500x3250x1480mm (59x128x58")	1800x3750x1600mm (71x148x63")	2000x3750x1600mm (79x148x63")
40-80 µm PE, OPP " W " Knife	Palletized Size (AxBxC): 1500x3450x1650mm (59x136x65")	1700x3450x1650mm (67x136x65")	2000x3950x1700mm (79x156x67")	2200x3950x1700mm (87x156x67")
Color: Mixed grey + RAL7010 + RAL7015	Weight (Net / Gross): 700 / 790 kg (1543 / 1742 lbs)	980 / 1010 kg (2161 / 2227 lbs)	1090 / 1250 kg (2403 / 2756 lbs)	1140 / 1320 kg (2513 / 2910 lbs)

* For DIN A4 form and ProMotion 40 series real working speed depends on the product dimensions and the film type.



Park Endüstriyel Ürünler Sanayi Uluslararası İç ve Dış Tic. Ltd. Şti.
 Atalar Cad. Gamze Sk. No: 13/A 34862
 Atalar / Kartal / İstanbul / Türkiye
 Tel: +90 216 353 54 66 Mobile / WhatsApp: +90 533 690 05 55
 info@packpark.com.tr www.packpark.com.tr