

# ULTIMATE MOTION D SERIES

High speed continuous PE sleeve wrapper



Ultimate<sup>®</sup> is a registered trademark of PackPark

# ULTIMATE MOTION D SERIES

## High speed continuous PE sleeve wrapper

### ADVANTAGES

- High speed automation with continuous-motion packaging system
- Two direction vertical & horizontal Servo motor driven cross seal
- Flexible and soft operation for vertical stacked package groups without slip out
- Without time loss for complete sealing sequence by vertical & linear motion operation
- Extreme precision and consistency with the sealing quality and package length positioning
- Easy integration to the production lines with adjustable in-feed conveyor
- The out put capacity can reach up to 50 packs/min. depending on the film, package dimension
- Low energy consumption
- More controls and cautions for more efficient production
- Advantage of easy and fast film roll change
- Instead of pneumatic systems controlling weakness, servo motor gives more powerful solution about controlling pressure and high quality sealing

### FEATURES

- Two direction vertical & horizontal servo motor driven cross seal,
- Seal bar length 640mm
- Maximum cross seal height 200mm
- Maximum film width: 700mm
- Linear speed of the conveyors: 20 mt / min

- The latest Siemens or Delta environment for all intelligent controls
- Touch panel with different languages and easy graphic controls for operator
- Installed power: 400V. 3 phase, 6kW, 9 Amps.
- Encoder controlled length adjustment for automatic synchronization with the speed
- Low film consumption
- Advantage of film tension release on the cross-sealing point
- Optional height adjustable "cross-sealing" feature (Optional motorized control)
- Control of optional integrated external conveyor from operator panel.
- Consistency in packaging quality
- Integrated automatic external in-feed belt control.
- Easy change over between different product sizes and speed changes
- Recipe memory application against different package dimensions
- Automatic film dispenser with tension control
- Complete closed housing with limit switch controlled windows for security
- Photocell controlled package in-feed
- ISO 9001 quality standard with the relevant norm's confirmations,
- Festo Pneumatics, Moeller, Siemens electric components
- CE marking,
- Manufacturer's guarantee for spare part stock and after sales support,
- One year warranty on non-wearable parts
- Color: Metallic dark gray (RAL code: custom color)



### Technical Specifications

#### MOTION 60-D

#### MOTION 80-D

#### MOTION 100-D

Seal Bar Length mm / inches:	640 mm - 25"	800 mm - 31,5"	1000 mm - 39,4"
Max. Film Width mm / inches:	700mm - 27,5"	900mm - 35,4"	1100mm - 43,3"
Machine Weight Net - kg / lbs:	900 kg - 1984 lbs	N / A	N / A
Mac. Weight Crated - kg / lbs:	1130 kg - 2491 lbs	N / A	N / A
Power Supply:	400 V 9 A 3 phase	400 V 9 A 3 phase	400 V 9 A 3 phase
Consumption Max / Average	6 kW / 5 kW	N / A	N / A
Dimensions mm (axbxcxdxextfxh)	3310x2010x1810	N / A	N / A
Max. Jaw Height mm / inches	200 mm - 7,9"	200 mm - 7,9"	200 mm - 7,9"
Max. Capacity:	50 packs / min	50 packs / min	40 packs / min
Color - RAL:	Metallic Dark gray	Metallic Dark gray	Metallic Dark gray

